DATE:					American Panel		
REP#:	INTERNAL SALE	S:					
O Quote #	O Quote only	O Quote only O Drawings		WALK-IN SPEC CHEC		CHECKLIST	
PROJECT:			LOCA	ATION:			
COMPANY:	ADDRESS:		CITY:		STATE:	ZIP:	
CONTACT:	PHONE:		EMAIL:				
TYPE OF ROOM: O Cooler	O Freezer	O Beer Cooler	O Combination	O Other			
INSTALLATION LOCATION: O In	door O Outdoor	INSULATION TYP	PE (UL FLAME SPRE	AD 20): 04"	FIP Urethane	○ 5" FIP Urethane	
IF OUTDOOR: O Free Standing	ng O Door Opens	to Interior	O Door Opens t	o Exterior			
	Length		•				
COMBINATION SIZE: Cooler Wie	=	_			her Width	Length	
FLOOR SPECS			INTERIOR FINISH	I	EXTERIOR F	INISH	
O Smooth Aluminum		O Recessed - Pit Depth			O Acrylume		
O 16 Ga. Stainless Steel	O Thermal Break w/Insulated Slab		O .040 White Smooth Alum.			e Smooth Alum.	
O 1/8" DATP	O 1 3/4" Vinyl Screeds		O .040 White Stucco Alum.				
O .125 Smooth Alum.	O Flat Bottom Panels (Alum. angle)		O .032 Stucco Alum.				
O Plywood Underlayment	O 14 Ga. Galv. (Non NSF)		22 Ga. Stainles20 Ga. Stainles		O 22 Ga. Sta		
O 1/4" O 1/2" O 3/4"		O Slab Insulation & Visqueen			O 20 Ga. Sta		
AmeriTuff Structural Floor	O Included O By	Others	O 24 Ga. Designe	er Color Gal.	○ 24 Ga. De	esigner Color Gal.	
DOOR SPECS			REFRIGERATION	SYSTEM			
O Quantity:			System Location:	O Indoor	O Outo	door	
O Hinged: W H	_ Hinge: OR O	L O Inswing	O On Slab	On Bld. Ro	of On V	Walk-In Roof	
O Hinged: W H	_ Hinge: OR O	L O Inswing	Туре:	O Air Cooled	○ Wate	er Cooled	
O Sliding: W H	_ Slide: OR O	L	O Remote Pre-ass				
O Sliding: W H	_ Slide: OR O	L	O Remote Quick		-		
O Slide Type: O Manual O Electric			Top Mount Quick Connect (Roof Penetration)Top Mount Quick Connect (Wall Penetration)				
O Glass Hinged: WH	_ Hinge: OR O	L	O Zero Roof Line	ck Connect (Wa	ıı renetration)		
O Framed Opening - Door by Oth	ers: W	Н	O Deluxe Pre-asse	embled Remote	Unit		
O Other: W H	_ Hinge: OR O	L O Inswing	Condensing Unit E		J		
			Voltage		cle	Phase	
ACCESSORIES			Evaporator Unit El	=			

ACCESSORIES	
O IC Controller (Standard)	O Interior Ramp
O IC+ Controller	O Exterior Ramp
O Extended Probe	O Prison Package
O Secondary Probe	O Foot Treadle
O Panic Alarm w/Internal Switch	O Spring Door Closer
O 4' LED Lighting - Qty:	O 3 Hinges/Door
O 18" LED Lights - Qty:	O Dial Thermometer
O LED Globe Light	O Spring Hinges
O Closure Panel: Height:	O Pressure Relief Vent (Cooler)
O Trim Strips	O Non-skid Floor Strips
O S/S Bumper Rail: O Int O Ext	O Door Locking Bar
O Vinyl Bumper Rail: O Int O Ext	O Strip Curtain
O Wainscot: Metal:	3-Way Switch

O 4-Way Switch

Other: _

O CCI ClearVu Swing Curtain

O 14"x14" Viewport Window

O 14"x24" Viewport Window

O Rain Roof Membrane

O Door Raincap (External Units)

O Interior O Exterior

O Coved Base: O Alum O S/S

O Interior O Exterior

O Jambguards: Height:_____

O S/S O 1/10" Treadplate

O Kickplate: Height: ____

Height:___

NOTES:												
O Other:												
Center Mount (Cooler Evaporator											
One Year Labor Warranty on Refrigeration Systems												
Winterization Controls												
O 18" High Comp												
Compressor Co												
REFRIGERATION												
Voltage	Cycle _	Phase	_									
Evaporator Unit Ele		D.										
Voltage	Cycle _	Phase	_									
Condensing Unit E	lectrical:											
O Deluxe Pre-asse	embled Remote Unit											
 Remote Pre-assembled Remote Quick Connect' Pre-charged Line Top Mount Quick Connect (Roof Penetration) Top Mount Quick Connect (Wall Penetration) Zero Roof Line 												
									•	O Air Cooled	○ Water Cooled	
											On Walk-In Roof	
									,	- 1114001	- Cutacoi	

5800 SE 78th St. Ocala, FL 34472 | Ph. 800.327.3015 www.americanpanel.com | Sales@americanpanel.com