

AMERICAN PANEL BLAST CHILLERS

MODEL NUMBER	TYPE	NUMBER OF PANS	PAN SIZE	CHILLING CAPACITY ¹ [LBS]	FREEZING CAPACITY ² [LBS]	REF. CAPACITY ³ [BTU/HOUR]	REF. SYSTEM	ELECTRICAL SUPPLY	NEMA	WORKING DIM SHIPPING DIM WxDxH	SHIPPING WEIGHT [LBS]	APC CONDENSING UNIT DENOM.	BOHN COND. UNIT AIR COOLED	BOHN COND. UNIT WATER COOLED
AP3BCF30-1 D	BLAST CHILLER & SHOCK FREEZER	3	12"X20"X2.5"	30	18	4000	MEDIUM / LOW TEMP	120 VAC, 10A, 1PH, 60HZ ,15A CIRCUIT	5-15P	25-1/2"x25-7/8"x36" 31"x31"x44"	270	N/A		
AP5BCF45-2 D	BLAST CHILLER & SHOCK FREEZER	5	12"X20"X2.5"	45	27	6600	MEDIUM / LOW TEMP	208 VAC, 7A, 1PH, 60HZ ,15A CIRCUIT	6-15P	29-1/2"x28-1/2"x35-7/8" 35"x34"x44"	350	N/A		
AP7BCF70-2	BLAST CHILLER & SHOCK FREEZER	14 \ 7	12"X20"X2.5" / 18"X26"	70	60	13000	MEDIUM / LOW TEMP	208 VAC, 12A, 1PH, 60HZ ,20A CIRCUIT	L6-20P	32-5/16"x41-1/16"x57-40"x47"x65"	635	N/A		
AP7BCF70-2-C	BLAST CHILLER & SHOCK FREEZER	7 \ 7	12"X20"X2.5" / 18"X26"	70	60	13000	MEDIUM / LOW TEMP	208 VAC, 12A, 1PH, 60HZ ,20A CIRCUIT	L6-20P	59"x34"x44" (36" 65"x42"x52"	745	N/A		
AP10BCF100-2	BLAST CHILLER & SHOCK FREEZER	10	12"X20"X2.5"	100	60	13000	MEDIUM / LOW TEMP	208 VAC, 12A, 1PH, 60HZ ,20A CIRCUIT	L6-20P	29-9/16"x34"x63-3/16" 35"x42"x71"	585	N/A		
AP12BCF110-3	BLAST CHILLER & SHOCK FREEZER	24 \ 12	12"X20"X2.5" / 18"X26"	110	90	20000	MEDIUM / LOW TEMP	208 VAC, 10A, 3PH, 60HZ ,20A CIRCUIT	L15-20P	32-5/16"x41-1/8"x75" 38"x47"x83"	825	N/A		
AP20BCF200-3	BLAST CHILLER		12"X20"X2.5"		N/A			VAC, A, PH, 60HZ ,A CIRCUIT			0	(0) N/A		
AP20BCF200-3	BLAST CHILLER & SHOCK FREEZER	MAXIMUM RACK DIMENSIONS: 26" x 32" x 71.5"	12"X20"X2.5"	200	120	25000	MEDIUM / LOW TEMP	208 VAC, 19.5A, 3PH, 60HZ ,30A CIRCUIT	N/A	47-5/8"x42-3/4"x93-7/8" 53"x51"x99"	1,220	N/A		
AP20BC200-2	BLAST CHILLER	MAXIMUM RACK DIMENSIONS: 26" x 32" x 71.5"	12"X20"X2.5"	200	N/A	25000	MEDIUM TEMP	208 VAC, 8A, 1PH, 60HZ ,15A CIRCUIT	N/A	47-5/8"x42-3/4"x88-1/4" 53"x51"x94"	1,000	RCU4BC	BCH0045M*ACZ	ZWN045X6*
AP20BCF200-2	BLAST CHILLER & SHOCK FREEZER	MAXIMUM RACK DIMENSIONS: 26" x 32" x 71.5"	12"X20"X2.5"	200	120	25000	MEDIUM / LOW TEMP	208 VAC, 8A, 1PH, 60HZ ,15A CIRCUIT	N/A	47-5/8"x42-3/4"x88-1/4" 53"x51"x94"	1,000	RCU3BCF	BBT0301M6*AP	WS0301M6*A
AP24BC250-3	BLAST CHILLER	MAXIMUM RACK DIMENSIONS: 30" x 37" x 72"	12"X20"X2.5"	250	N/A	25000	MEDIUM TEMP	208 VAC, 8A, 3PH, 60HZ ,15A CIRCUIT	N/A	54-3/4"x46-1/4"x88-1/2" 60"x53"x97"	1,240	RCU4BC	BCH0045M*ACZ	ZWN045X6*
AP24BCF300-3	BLAST CHILLER & SHOCK FREEZER	MAXIMUM RACK DIMENSIONS: 30" x 37" x 72"	12"X20"X2.5"	300	180	50000	MEDIUM / LOW TEMP	208 VAC, 8A, 3PH, 60HZ ,15A CIRCUIT	N/A	54-3/4"x46-1/4"x88-1/2" 60"x53"x97"	1,240	RCU7BCF	BCH0076M*ABX	WS0751M6*A
AP24BC250-3-R	BLAST CHILLER	(1) 202 / iCombi RATIONAL RACK	12"X20"X2.5"	250	N/A	25000	MEDIUM TEMP	208 VAC, 8A, 3PH, 60HZ ,15A CIRCUIT	N/A	54-3/4"x47"x85-1/2" 60"x53"x97"	1,200	RCU4BC	BCH0045M*ACZ	ZWN045X6*
AP24BCF300-3-R	BLAST CHILLER & SHOCK FREEZER	(1) 202 / iCombi RATIONAL RACK	12"X20"X2.5"	300	180	50000	MEDIUM / LOW TEMP	208 VAC, 8A, 3PH, 60HZ ,15A CIRCUIT	N/A	54-3/4"x47"x85-1/2" 60"x53"x97"	1,200	RCU7BCF	BCH0076M*ABX	WS0751M6*A

¹ - 160°F TO 38°F WITHIN 90 MIN ² - 160°F TO 0°F WITHIN 240 MIN ³ - AT EVAP. TEMP. 14°F AND COND. TEMP. 105° * - ADD "C" FOR 208-230V/60HZ/3PH OR ADD "D" FOR 460V/60HZ/3PH MODEL