



**BLAST CHILLER / SHOCK FREEZER  
(Self-Contained)  
Model: AP5BCF45-2**

JOB: \_\_\_\_\_  
ITEM #: \_\_\_\_\_  
QTY. REQUIRED: \_\_\_\_\_

AIA FILE #: \_\_\_\_\_

SPEC #: \_\_\_\_\_

**BLAST CHILLER / SHOCK FREEZER (Self-Contained)**  
Model: AP5BCF45-2

**SPECIFICATIONS**

**SCOPE:** This specification covers the model AP5BCF45-2 HURRICHILL™ Blast Chiller/Shock Freezer. This compact unit has a self-contained, air-cooled refrigeration system and is complete with all required controls and accessories. Several options are also available.

**GENERAL:** The unit has 5 pan slides for a total pan capacity of (5) 12" x 20" x 2 1/2" steam table pans. A core temperature probe is provided for accurate control of temperature within the product.

**PERFORMANCE:** Blast chilling (soft or hard) lowers the food core temperature from 160°F to 38°F within 120 minutes. Shock freezing lowers the food core temperature from 160°F to 0°F within 4 hours. Chilling/Freezing times will vary somewhat, depending on the food quantity, initial temperature, density, moisture content, specific heat, and type of container. The airflow has a high velocity, indirect pattern designed to cool all levels at identical rates. Time/temperature chilling and freezing rates meet or exceed all FDA, NSF and state regulations.

**CONSTRUCTION:** The chilling/freezing cabinet is constructed of polished type 304 stainless steel, with 2-3/4" of CFC-free, high density polyurethane insulation. The interior panels have a mirror finish and interior bottom corners are fully rounded. The door is equipped with a removable magnetic gasket. The door is hinged on operator's left. All motors are sealed ball bearing wash-down type. A 6' long four wire cord set with a NEMA L6-20P plug is provided.

**REFRIGERATION SYSTEM:** The self-contained refrigeration system includes a condensing unit using R-404A refrigerant. The evaporator temperature range is +25°F to -40°F. The compressor is a semi-hermetic type with inherent overload protection.

**MICROPROCESSOR CONTROL SYSTEM:** The solid state electronic control panel is user friendly, easy to read and can be set for one of the unit's three cycles. All settings are programmable by the user.

**MODES OF OPERATION:**

**Automatic:** The provided core temperature probe monitors the temperature of the product and ends the cycle when the product is at a safe temperature.

**AVAILABLE OPERATING CYCLES:**

- Soft Chill:** The air temperature is held right above the food freezing point for the entire duration of the cycle, ideal for delicate food items.
- Hard Chill:** The air temperature changes during the cycle to chill the product quickly, uniform and without freezing it.



**Note:** Unit shown with optional legs.

- Shock Freezing:** This cycle is designed to avoid damage to the food structure, keeping the food free of large ice crystals. The air temperature is lowered to and held at -25°F. The freezing cycle is completed when the food core temperature reaches 0°F.
- Holding:** At the end of any cycle (soft/hard chilling, shock freezing or thawing), the unit will automatically switch to a holding mode which will keep food at 38°F (chilled/thawed) or 0°F (frozen) until the STOP button is pressed to end the cycle.

**ADDITIONAL FEATURES:**

- Defrost:** A manual defrost can be performed at any time.



BLAST CHILLER / SHOCK FREEZER (Self-Contained)

Model: AP5BCF45-2

SPEC #:

AIA FILE #:

# Details and Dimensions

## BLAST CHILLER / SHOCK FREEZER (Self-Contained) Model: AP5BCF45-2

**COMPARTMENT SECTION**

E ELECTRICAL CONNECTION  
D DRIP PAN DRAIN  
P DRAIN PAN

DIMENSIONS	OUTSIDE			INSIDE			DEPTH WITH DOOR OPENED	SHIPPING WEIGHT [LBS.]
	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
ENGLISH	29-1/2"	28-1/2"	36"	25-1/2"	13-3/4"	15-3/8"	55-1/2"	373
METRIC [MM]	749	724	915	648	350	391	1410	

MODEL	MAXIMUM LOAD PER CYCLE [LBS]			ELECTRICAL TOTAL					COMPRESSOR HP
	CHILL (120 MIN)	CHILL (90 MIN)	FREEZE (240 MIN)	VOLTS	PH.	HZ.	AMPS.	NEMA	
AP5BCF45-2	63	45	27	208	1	60	7.0	6-15P	3/4

**OPTIONS:**

**Stationary Legs:** 3" casters are standard. 6" high stainless steel legs are optional. Heavy duty casters, two with brakes, are optional.

**Wire Racks:** Full width wire rack(s) to accommodate pans smaller than 12" x 20".

**INSTALLATION:** A detailed installation manual is provided. It must be carefully followed to ensure proper operation and to protect your rights under the warranty.

**WARRANTY:** The warranty covers all parts found to be defective and the labor required to replace them for a period of one year from the date of shipment. The compressor only is covered for an additional period of four years, as a part only, no labor.

4.12.2018

American Panel Corporation | 5800 S.E. 78th Street, Ocala, Florida 34472-3412 | Phone: 1-800-327-3015 • (352) 245-7055 | Fax: (352) 245-0726