



QUOTATION REQUEST FORM (FOAMED-IN-PLACE CONSTRUCTION)

Name: _____
 Company: _____
 Address: _____
 Phone: _____
 Fax #: _____

Date: _____
 Job: _____
 Location: _____
 Marketing Agent: _____
 APC Sales Associate: _____

TYPE OF ROOM: Cooler Beer Cooler Freezer Combination Other _____
 NOMINAL OVERALL SIZE (Outside Dimensions): Width _____ x Length _____ x Height _____
 ACTUAL OVERALL SIZE (Outside Dimensions): Width _____ x Length _____ x Height _____
 COMBINATION: Cooler (W _____ x L _____) Freezer (W _____ x L _____) Other (W _____ x L _____)
 INSTALLATION: Inside Outside (Go To Outdoor Accessories Section) CONSTRUCTION: NSF
 INSULATION: 4" Foamed-In-Place Urethane, UL Flame Spread 20 Other _____ Qty. _____ Width _____ x Height _____

FLOOR:

- Without Floor (Vinyl Screenshot Provided)
- Cooler Floorless/Freezer with Floor (Select Type)
- .100 Smooth Aluminum
- 14 Ga. Galvanized Steel (non-NSF)
- 16 Ga. Ameri-Tuff With Non-Skid Strips in Aisle
- 1/8" Diamond Aluminum Treadplate Floor Surface
- 16 Ga. Stainless Steel With Non-Skid Strips in Aisle
- 1/8" Diamond Aluminum Treadplate on top of Galv. Steel
- 3/16" Diamond Aluminum Treadplate on top of Galv. Steel
- Insulated Slab by Others

Insulation by APC Others

FINISH:

	INT.	EXP.	UNEXP.
<input type="checkbox"/> 26 Ga. Stucco Galvanized Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> .032 Stucco Emb. Aluminum	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> .040 Stucco Emb. Aluminum	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> .040 White Stucco Aluminum	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 26 Ga. Stucco White Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 26 Ga. Stucco Choco. Brown Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 24 Ga./22 Ga. Flat Galvanized Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 26 Ga. Stucco Galvalume	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 22 Ga. Stainless Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> 20 Ga. Stainless Steel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note: Exterior top of roof and bottom of floor are 26 Ga. Stucco Embossed Galvanized Steel as standard.

WALK-IN DOORS:

- Standard Size Flush Door Cooler Qty. _____ Freezer Qty. _____
 - Special Size Flush Door Cooler Qty. _____ Freezer Qty. _____
- Size: _____

OPTIONAL HARDWARE:

- Kickplate Int. _____ Ext. _____
- Ramp Int. _____ Ext. _____
- Heated View Window Thermal Strip Curtain
- Deadbolt Lock Digital Thermometer
- Deadbolt Lock with Institutional Handle Spring Loaded Hinge
- Foot Treadle Extra Hinge
- Other: _____ 3-Way Light Switch

SPECIAL DOORS:

- Hinged Solid Reach-In Qty. _____ Width _____ x Height _____
- Hinged Glass Qty. _____ Width _____ x Height _____
 - Lights Shelves Heaters
- Sliding Glass Qty. _____ Width _____ x Height _____
- Insulated Sliding Doors Qty. _____ Width _____ x Height _____
 - Manual Electric
 - Single Slide Bi-Parting Slide

ACCESSORIES:

- Audio-Visual Temperature Alarm
- Heated Pressure Relief Vent
- Extra Incandescent Vapor Proof Lights: Qty. _____
- 4 Ft. Fluorescent Lights: Cooler Qty. _____ Freezer Qty. _____
- Roof Support Channel (Indoor Only)
- Interior Support Steel Structure
- Closure Panel _____
- Trim Strips _____
- Corner Guard _____
- Bumper Rail, 22 Gauge Stainless Steel _____
- Bumper Rail, Vinyl with Aluminum Extrusion _____
- Wall Protection _____
- Other _____

OUTDOOR ACCESSORIES:

- Rain Roof, Membrane Type
 - Flat Pitched One-Way Pitched Two-Way
- Rain Roof, Metal Type, Flat
- Door Locking Bar
- Door Rain Cap
- Hurricane Code Floor Angle

REFRIGERATION:

- Condensing Unit Location: Indoors Outdoors
 - On Slab On Bldg Roof On Walk-in Roof
- Hermetic Air Cooled Water Cooled
- Semi-Hermetic Air Cooled Water Cooled
- Basic Remote
- Remote Quick Connect _____ ft. Precharged Lines (40' Max.)
- Top Quick Connect (Roof Penetration)
- Top Quick Connect (Wall Penetration)
- Pre-Assembled Remote
- Deluxe Pre-Assembled Remote (includes stand)
- By Others

VOLTAGE: 115/60/1 208/60/1 230/60/1
 208/230/60/3 Other 50 cycle

REFRIGERATION ACCESSORIES:

- Compressor Cover Winterization Controls
- Compressor Mounting Stand UL Outdoor Cover
- Pitch Pans 18" High Comp. Stand
- Mounting Curbs Other
- One Year Service on Pre-Charged System
- 5-Year warranty deduct (out of U.S.)